

# Standard Authorization Request Form

Title of Proposed Standard: Project 2009-02: Real-time Tools

Request Date: May 11, 2009

Approved by SC: June 4, 2009

| SAR Requester Information                |                   | <b>SAR Type</b> ( <i>Check a box for each one that applies.</i> ) |                                 |
|--|-------------------|---|---------------------------------|
| Name:                                    | Jack Kerr         | Х   | New Standard(s)                 |
| Primary Contact: Dominion Virginia Power |                   |   | Revision to existing Standard   |
| Telephone:                               | 1.804.273.3393    |   | Withdrawal of existing Standard |
| Fax:                                     | 1.804.273.2405    |   |                                 |
| E-mail:                                  | jack.kerr@dom.com |   | Urgent Action                   |

**Purpose** (Describe what the standard action will achieve in support of bulk power system reliability.)

The new standard or standards will establish requirements for the functionality, performance, and management of Real-time tools for Reliability Coordinators, Transmission Operators, and Balancing Authorities for use by their System Operators in support of reliable System operations.

**Industry Need** (Provide a justification for the development or revision of the standard, including an assessment of the reliability and market interface impacts of implementing or not implementing the standard action.)

According to the *Final Report on the August 14, 2003 Blackout in the United States and Canada: Causes and Recommendations,* dated April 2004, a principal cause of the August 14 blackout was a lack of situational awareness, which was in turn the result of inadequate reliability tools. In addition, the failure of control computers and alarm systems, incomplete tool sets, and the failure to supply network analysis tools with correct System data on August 14 contributed directly to this lack of situational awareness. Also, the need for improved visualization capabilities over a wide geographic area has been a recurrent theme in blackout investigations.

Recommendation 22 of the Blackout Report states "Evaluate and adopt better real-time tools for operators and reliability coordinators." NERC's Operating Committee formed the Real-time Tools Best Practices Task Force (RTBPTF) to evaluate real-time tools and their usage within the industry. The Task Force produced a report "*Real-Time Tools Survey Analysis and Recommendations*", dated March 13, 2008 that included recommendations for the functionality, performance, and management of Real-time tools.

This SAR addresses selected recommendations in the RTBPTF Report as determined by the Real-time Best Practices Standards Study Group: Project 2009-02.

Brief Description (Provide a paragraph that describes the scope of this standard action.)

The scope of the SAR is to establish requirements for the functionality, performance, and management of tools used in support of Real-time System Operations. The intent is to describe 'what' needs to be done but not 'how' to do it.

**Detailed Description** (Provide a description of the proposed project with sufficient details for the standard drafting team to execute the SAR.)

Develop a standard(s) to require the following functionality:

• Alarming – Applications or methods that emit Real-time visible and audible signals to alert Operators to events and conditions affecting the state of the Bulk Electric System (BES).

• Telemetry – Applications and methods that provide status and analog values in Realtime or near-Real-time operation.

• Network analysis – Applications and methods to be used for determining the current state of the system and simulating the impact of 'what if' system events on the current

#### or future state of the system.

Develop a standard(s) to require that responsible entities meet identified performance metrics for the above listed functionalities including but not limited to the consideration of:

- Availability
- Quality

Those entities shall also have procedures for the above listed functionalities including but not limited to the consideration of:

- Change management
- Maintenance coordination
- Failure notification

Revise the Glossary definition of Real-time given that the acquisition and dissemination of operating data has inherent time delays. The current definition of Real-time is: Current time, as opposed to future time.

## **Reliability Functions**

| The Stand | The Standard will Apply to the Following Functions (Check box for each one that applies.) |  |  |
|-----------|---|--|--|
| Х         | Reliability<br>Coordinator  | Responsible for the real-time operating reliability of its Reliability<br>Coordinator Area in coordination with its neighboring Reliability<br>Coordinator's wide area view.                                 |  |
| Х         | Balancing<br>Authority  | Integrates resource plans ahead of time, and maintains load-<br>interchange-resource balance within a Balancing Authority Area<br>and supports Interconnection frequency in real time.                       |  |
|           | Interchange<br>Authority  | Ensures communication of interchange transactions for reliability<br>evaluation purposes and coordinates implementation of valid and<br>balanced interchange schedules between Balancing Authority<br>Areas. |  |
|           | Planning<br>Coordinator   | Assesses the longer-term reliability of its Planning Coordinator Area.   |  |
|           | Resource<br>Planner   | Develops a >one year plan for the resource adequacy of its specific loads within a Planning Coordinator area.  |  |
|           | Transmission<br>Planner   | Develops a >one year plan for the reliability of the interconnected<br>Bulk Electric System within its portion of the Planning Coordinator<br>area.  |  |
|           | Transmission<br>Service<br>Provider   | Administers the transmission tariff and provides transmission services under applicable transmission service agreements (e.g., the pro forma tariff).  |  |
|           | Transmission<br>Owner   | Owns and maintains transmission facilities.  |  |
| Х         | Transmission<br>Operator  | Ensures the real-time operating reliability of the transmission assets within a Transmission Operator Area.  |  |
|           | Distribution<br>Provider  | Delivers electrical energy to the End-use customer.  |  |
|           | Generator<br>Owner  | Owns and maintains generation facilities.  |  |
| Х         | Generator<br>Operator   | Operates generation unit(s) to provide real and reactive power.  |  |
|           | Purchasing-<br>Selling Entity   | Purchases or sells energy, capacity, and necessary reliability-<br>related services as required.   |  |
|           | Market<br>Operator  | Interface point for reliability functions with commercial functions.   |  |
|           | Load-<br>Serving<br>Entity  | Secures energy and transmission service (and reliability-related services) to serve the End-use Customer.  |  |

## Reliability and Market Interface Principles

| Appl | Applicable Reliability Principles (Check box for all that apply.)  |  |  |
|------|--|--|--|
| Х    | 1.   | Interconnected bulk power systems shall be planned and operated in a coordinated manner to perform reliably under normal and abnormal conditions as defined in the NERC Standards.               |  |
| х    | 2.   | The frequency and voltage of interconnected bulk power systems shall be controlled within defined limits through the balancing of real and reactive power supply and demand.                     |  |
| Х    | 3.   | Information necessary for the planning and operation of interconnected bulk power systems shall be made available to those entities responsible for planning and operating the systems reliably. |  |
|      | 4.   | Plans for emergency operation and system restoration of interconnected bulk power systems shall be developed, coordinated, maintained and implemented.   |  |
| Х    | 5.   | Facilities for communication, monitoring and control shall be provided, used and maintained for the reliability of interconnected bulk power systems.  |  |
|      | 6.   | Personnel responsible for planning and operating interconnected bulk power systems shall be trained, qualified, and have the responsibility and authority to implement actions.                  |  |
| х    | 7.   | The security of the interconnected bulk power systems shall be assessed, monitored and maintained on a wide area basis.  |  |
|      | 8.   | Bulk power systems shall be protected from malicious physical or cyber attacks.  |  |
|      |  | e proposed Standard comply with all of the following Market Interface<br>es? (Select 'yes' or 'no' from the drop-down box.)  |  |
|      |  | ability standard shall not give any market participant an unfair competitive<br>ntage. Yes   |  |
| 2. A | 2. A reliability standard shall neither mandate nor prohibit any specific market structure. Yes  |  |  |
|      | 3. A reliability standard shall not preclude market solutions to achieving compliance with that standard. Yes  |  |  |
| ir   | 4. A reliability standard shall not require the public disclosure of commercially sensitive<br>information. All market participants shall have equal opportunity to access commercially<br>non-sensitive information that is required for compliance with reliability standards. Yes |  |  |

## **Related Standards**

| Standard No. | Explanation |
|--------------|-------------|
|              |             |
|              |             |
|              |             |
|              |             |

#### **Related SARs**

| SAR ID | Explanation |  |
|--------|-------------|--|
|        |             |  |
|        |             |  |
|        |             |  |
|        |             |  |
|        |             |  |
|        |             |  |
|        |             |  |
|        |             |  |

# Regional Variances

| Region | Explanation |
|--------|-------------|
| ERCOT  |             |
| FRCC   |             |
| MRO    |             |
| NPCC   |             |
| SERC   |             |
| RFC    |             |
| SPP    |             |
| WECC   |             |