

BAL-013-1 – Large Loss of Load Performance Standard Background Document

January 2012

RELIABILITY | ACCOUNTABILITY









3353 Peachtree Road NE Suite 600, North Tower Atlanta, GA 30326 404-446-2560 | www.nerc.com

Table of Contents

Contents

Table of Contents	. 2
Introduction	. 3
Background and Rationale by Requirement	. 3
Requirement 1	. 3

Introduction

Since loss of large loss of load occurs and impacts all Balancing Authorities throughout an Interconnection, BAL-013-1 was created to specify recovery actions and associated timeframes. This document provides background on the development and implementation of BAL-013-1, Large Loss of Load Performance. The intent is to explain the rationale and considerations for the requirements and their associated compliance information. The original Standards Authorization Request (SAR) approved by the industry presumes there is presently sufficient Contingency Reserve in all the North American Interconnections. The underlying goal of the SAR was to update the standard to make the measurement process more objective and to provide information to the Balancing Authority or Reserve Sharing Group, such that the parties would better understand the use of Contingency Reserve to balance resources and demand and return Interconnection frequency within defined limits following a Large Loss of Load Event.

Background and Rationale by Requirement

Requirement 1

- **R1.** Each Balancing Authority or Reserve Sharing Group shall correct its ACE following each Large Loss of Load Event within 15 clock minutes of the initiation of that event, as follows:
 - If the Balancing Authority or Reserve Sharing Group's ACE value just prior to a Large Loss of Load Event is negative or equal to zero, the Balancing Authority or Reserve Sharing Group shall return its ACE to zero.
 - If the Balancing Authority or Reserve Sharing Group's ACE value just prior to a Large Loss of Load Event is positive, the Balancing Authority or Reserve Sharing Group shall return its ACE to its pre-event value.

Background and Rationale

Requirement R1 is intended to provide the information needed to determine if the BA or Reserve Sharing Group corrected its ACE in recovering from a Large Loss of Load Event, and if they did so within the 15-minute time period allowed by the requirement.

The SDT has mirrored the reporting threshold from BAL-002-2. This will allow for consistent monitoring of system performance since a single threshold will be used for all Contingencies.

The 15 minutes for recovery was chosen to be consistent with the 15-minute Disturbance recovery period for BAL-002, Loss of Resources. The 15-minute recovery period is one that has long been used in BAL-002, and goes back to initial NERC policy.