Standard Development Timeline

This section is maintained by the drafting team during the development of the standard and will be removed when the standard becomes effective.

Description of Current Draft

This version of Reliability Standard IRO-009 is posted for final ballot to address the recommendations of the Project 2012-09 Interconnected Reliability Operations Five-Year Review Team (FYRT). That review resulted in a recommended drafting effort, which is being conducted by the Project 2015-06 Interconnection Reliability Operations and Coordination standard drafting team.

Completed Actions	Date
Standards Committee approved Standard Authorization Request (SAR) for posting	March 11, 2015
SAR posted for comment	March 16 – April 15, 2015
45-day formal comment period with ballot	May 21– July 9, 2015

Anticipated Actions	Anticipated Dates
Final ballot	July 2015
NERC Board of Trustees (Board) adoption	August 2015

Standard IRO-009-21 — Reliability Coordinator Actions to Operate Within IROLs New or Modified Term(s) Used in NERC Reliability Standards

This section includes all new or modified terms used in the proposed standard that will be included in the *Glossary of Terms Used in NERC Reliability Standards* upon applicable regulatory approval. Terms used in the proposed standard that are already defined and are not being modified can be found in the *Glossary of Terms Used in NERC Reliability Standards*. The new or revised terms listed below will be presented for approval with the proposed standard. Upon Board adoption, this section will be removed.

Term(s): None.

The rationale boxes will be moved to the Supplemental Material Section of the standard after the standard is adopted by the Board.

A. Introduction

- 1. Title: Reliability Coordinator Actions to Operate Within IROLs
- **2.** Number: IRO-009-42
- **3. Purpose:** To prevent instability, uncontrolled separation, or cascading outages that adversely impact the reliability of the interconnection by ensuring prompt action to prevent or mitigate instances of exceeding Interconnection Reliability Operating Limits (IROLs).

4. Applicability:

4.1. Reliability Coordinator.

5. **Proposed** Effective Date:

In those jurisdictions where no regulatory approval is required, the standard shallbecome effective on the latter of either April 1, 2009 or the first day of the firstcalendar quarter, three months after BOT adoption.

In those jurisdictions where regulatory approval is required, the standard shall become effective on the latter of either April 1, 2009 or the first day of the first calendar quarter, three months after applicable regulatory approval. See the Implementation Plan for IRO-009-2.

B. Requirements

Rationale for revisions to Requirements R1: The standard drafting team (IRO SDT) revised this requirement by combining IRO-009-1 Requirements R1 and R2 to form one requirement with two subparts to make the requirements more concise, as both requirements contained similar language.

R1. For each IROL (in its Reliability Coordinator Area) that the Reliability Coordinator identifies one or more days prior to the current day, the Reliability Coordinator shall have one or more Operating Processes, Procedures, or Plans that identify actions it the Reliability Coordinator shall take or actions-it-the Reliability Coordinator shall direct others to take (up to and including load shedding): that can be implemented in time to prevent exceeding those IROLs. (Violation Risk Factor: Medium) (Time Horizon: Operations Planning or Same Day Operations)

<u>1.1</u> <u>That can be implemented in time to prevent the identified IROL exceedance.</u>

1.1

1.2 **R2.** For each IROL (in its Reliability Coordinator Area) that the Reliability Coordinator identifies one or more days prior to the current day, the Reliability Coordinator shall have one or more Operating Processes, Procedures, or Plansthat identify actions it shall take or actions it shall direct others to take (up to and including load shedding) tTo mitigate the magnitude and duration of exceeding-

Standard IRO-009-24 — Reliability Coordinator Actions to Operate Within IROLs

<u>anthat IROL-IROL exceedance</u> such that the IROL <u>exceedance</u> is relieved within the IROL's T_v. (*Violation Risk Factor: Medium*) (*Time Horizon: Operations*-*Planning or Same Day Operations*)

Rationale for revisions to new Requirement R2 (previously Requirement R3): The IRO SDT revised the language of this requirement to improve clarity as well as consistency with similar NERC Board of Trustees (Board) approved standards, such as, TOP standard revisions (TOP-001-3 R14); "IROL exceedance," "Real-time monitoring," and "Real-time Assessments."

R23. When an assessment of actual or expected system conditions predicts that an IROL in its Reliability Coordinator Area will be exceeded, the Each Reliability Coordinator shall implement initiate one or more Operating Processes, Procedures, or Plans (not limited to the Operating Processes, Procedures, or Plans developed for Requirements R1) that are intended to prevent exceeding that an IROL exceedance as identified in the Reliability Coordinator's Real-time monitoring or Real-time Assessment.. (Violation Risk Factor: High) (Time Horizon: Real-time__Operations)

Rationale for revisions to new Requirement R3 (previously Requirement R4): The IRO SDT removed the term "without delay" from the requirement upon determining that the point of time at which the requirement is triggered is inherent in the requirement itself. The IRO SDT also revised the language of this requirement to improve clarity as well as consistency with similar Board approved standards, such as, TOP standard revisions (TOP-001-3 R14); "IROL exceedance," "Real-time monitoring," and "Real-time Assessments."

R4<u>R3</u>. When actual system conditions show that there is an instance of exceeding an IROL in its Reliability Coordinator Area, the Each Reliability Coordinator shall, without delay, act or direct others to act so that to mitigate the magnitude and duration of the instance of exceeding that an IROL exceedance is mitigated within the IROL's T_v, identified in the Reliability Coordinator's Real-time monitoring or Real-time Assessment. (Violation Risk Factor: High-) (Time Horizon: Real--time Operations)

Rationale for revisions to Requirement R4 (previously Requirement R5): The IRO SDT revised the language of this requirement for clarity as well as consistency with similar Board approved standards, such as TOP standard revisions (TOP-001-3 R18). The IRO SDT retained clarifying language to limit applicability to appropriate affected RCs.

R45. If unanimity cannot be reached on the value for an IROL or its T_v , eEach Reliability Coordinator that monitors that Facility (or group of Facilities) shall operate to, without delay, use—the most limiting IROL and T_v in instances where there is a difference in an IROL or its T_v between Reliability Coordinators that are responsible for that Facility (or group of Facilities) conservative of the values (the value with the least impact on reliability) under consideration. (Violation Risk Factor: High) (Time Horizon: Real-time Operations)

C. Measures

- M1. Each Reliability Coordinator shall have, and make available upon request, evidence to confirm that it has Operating Processes, Procedures, or Plans to address both preventing and mitigating the magnitude and duration of IROL exceedances instances of exceeding IROLs in accordance with Requirement R1 and Requirement R2. This evidence shall include a list of any IROLs (and each associated T_v) identified in advance, along with one or more dated Operating Processes, Procedures, or Plans that that will be used.
- M2. Each Reliability Coordinator shall have, and make available upon request, evidence to confirm that it initiated one or more Operating Processes, Procedures or Plans (not limited to the Operating Processes, Procedures, or Plans developed for Requirements R1) in accordance with Requirement R2. This evidence could include, but is not limited to, Operating Processes, Procedures, or Plans from Requirement R1, dated operating logs, dated voice recordings, dated transcripts of voice recordings, or other evidence.
- M3. Each Reliability Coordinator shall have, and make available upon request, evidence to confirm that it acted or directed others to act in accordance with Requirement R3. This evidence could include, but is not limited to, Operating Processes, Procedures, or Plans, dated operating logs, dated voice recordings, dated transcripts of voice recordings, or other evidence.M2. Each Reliability Coordinator shall have, and make available upon request, evidence to confirm that it acted or directed others to act in accordance with Requirement R3 and Requirement R4. This evidence could include, but is not limited to, Operating Processes, Procedures, or Plans from Requirement R1, dated operating logs, dated voice recordings, dated transcripts of voice recordings, or other evidence.
- **M43.** For a situation where Reliability Coordinators disagree on the value of an IROL or its T_v the Each Reliability Coordinator shall have, and make available upon request, evidence to confirm that it operated to the most limiting IROL and T_v in instances where there was a difference in an IROL or its T_v used the most conservative of the values under consideration, without delay. Such evidence could include, but is not limited to, dated computer printouts, dated operator logs, dated voice recordings, dated transcripts of voice recordings, or other equivalent evidence <u>in accordance with Requirement R4. (R5)</u>

Standard IRO-009-24 — Reliability Coordinator Actions to Operate Within IROLs

D. Compliance

1. Compliance Monitoring Process

1.1. Compliance Enforcement Authority:

"Compliance Enforcement Authority" means NERC or the Regional Entity, or any entity as otherwise designated by an Applicable Governmental Authority, in their respective roles of monitoring and/or enforcing compliance with mandatory and enforceable Reliability Standards in their respective jurisdictions.

1.2. For Reliability Coordinators that work for the Regional Entity, the ERO shall serve as the Compliance Enforcement Authority.

1.3. For Reliability Coordinators that do not work for the Regional Entity, the Regional Entity shall serve as the Compliance Enforcement Authority.

<u>1.2. Evidence Retention:</u>

The following evidence retention period(s) identify the period of time an entity is required to retain specific evidence to demonstrate compliance. For instances where the evidence retention period specified below is shorter than the time since the last audit, the Compliance Enforcement Authority may ask an entity to provide other evidence to show that it was compliant for the full-time period since the last audit.

The applicable entity shall keep data or evidence to show compliance as identified below unless directed by its Compliance Enforcement Authority to retain specific evidence for a longer period of time as part of an investigation.

The Reliability Coordinator shall retain evidence of Requirement R1; Requirement R2; Requirement R3; and Requirement for a rolling 12 months.

The Compliance Enforcement Authority shall keep the last audit records and all requested and submitted subsequent audit records, and any reported IROL violations submitted since the last audit.

1.3. Compliance Monitoring and Enforcement Program

As defined in the NERC Rules of Procedure, "Compliance Monitoring and Enforcement Program" refers to the identification of the processes that will be used to evaluate data or information for the purpose of assessing performance or outcomes with the associated Reliability Standard.

1.4. Additional Compliance Information None.

1.4. Compliance Monitoring Period and Reset Time Frame

Not applicable.

1.5. Compliance Monitoring and Enforcement Processes

Compliance Audits

Self-Certifications-

Spot Checking

Compliance Violation Investigations

- Self-Reporting
- **Complaints**

Exception Reporting

1.6. Data Retention

The Reliability Coordinator, shall keep data or evidence to show compliance asidentified below unless directed by its Compliance Enforcement Authority toretain specific evidence for a longer period of time as part of an investigation:

The Reliability Coordinator shall retain evidence of Requirement R1, Requirement R2, and Measure M1, for a rolling 12 months.

The Reliability Coordinator shall retain evidence of Requirement R3, Requirement R4, Requirement R5, Measure M2, and Measure M3 for a rolling 12 months.

The Compliance Enforcement Authority shall keep the last audit records and allrequested and submitted subsequent audit records, and all IROL Violation– Reports submitted since the last audit.

1.7. Additional Compliance Information

Exception Reporting: For each instance of exceeding an IROL for time greaterthan IROL T_V, the Reliability Coordinator shall submit an IROL Violation Reportto its Compliance Enforcement Authority within 30 days of the initiation of theevent.

2. Violation Severity Levels

Requirement	Lower	Moderate	High	Severe
R1				An IROL in its Reliability
				Coordinator Area was
				identified one or more days
				in advance and the
				Reliability Coordinator
				does not have an Operating
				Process, Procedure, or Plan
				that identifies actions to
				prevent that IROL
				exceedance (Part 1.1).
				OR
				An IROL in its Reliability
				Coordinator Area was
				identified one or more days
				in advance and the
				<u>Reliability Coordinator</u>
				does not have an Operating
				Process, Procedure, or Plan that identifies actions to
				mitigate that IROL
				exceedance within the
				IROL's T _v . (Part 1.2)An-
				$\frac{110L \text{ s } 1_{\text{V}}}{110L \text{ in its Reliability}}$
				Coordinator Area was
				identified one or more
				days in advance and the

R2		An IROL in its Reliability
		Coordinator Area was identified
		one or more days in advance and
		the Reliability Coordinator does
		not have an Operating Process,
		Procedure, or Plan that identifies
		actions to mitigate exceeding that
		IROL within the IROL's Tv. (R2)
R23		An assessment of actual or
-		expected system conditions
		predicted that an IROL in the
		Reliability Coordinator's Area
		would be exceeded, but nNo
		Operating Processes, Procedures,
		or Plans were-implemented
		initiated that were intended to
		prevent a predicted IROL
		exceedance as identified in the
		Reliability Coordinator's Real-
		time monitoring or Real-time
		Assessment. (R3)

Standard IRO-009-24 — Reliability Coordinator Actions to Operate Within IROLs

R34		Actual system	Actual system conditions showed
-		conditionsshowed that	that there was an IROL exceedance
		there was an instance of	in its Reliability Coordinator Area,
		exceeding an IROL in its	and that the IROL exceedance was
		Reliability Coordinator-	not resolved mitigated within the
		Area, and there was a	$\overline{\text{IROL's } T_{v}}$
		delay of five minutes or	
		more before acting or	
		directing others to act to-	
		mitigate the magnitude	
		and duration of the	
		instance of exceeding-	
		that IROL, however the	
		IROL was mitigated	
		within the IROL Tv.	

Requirement	Lower	Moderate	High	Severe
			<u>showed that there was an</u> instance of exceeding an- IROL in its Reliability- Coordinator Area, and there was a delay of five- minutes or more before- acting or directing others to act to mitigate the- magnitude and duration- of the instance of- exceeding that IROL, however the IROL was- mitigated within the- IROL-Tw- (R4)	showed that there was an instance of exceeding an IROL in its Reliability Coordinator Area, and that IROL was not resolved-within the IROL's T _V . (R4)
R <u>4</u> 5	Not applicable.	Not applicable.	Not applicable.	The most limiting IROL or its T _V was not operated to between Reliability Coordinators that are responsible for the Facility (or group of Facilities) associated with the IROL. There was a- disagreement on the value of the IROL or its Tv and the most conservative limi under consideration was- not used. (R5)

E. Regional Variances

None

I

F. Associated Documents

IROL Violation ReportNone.

Version History

Version	Date	Action	Change Tracking
1	October 17, 2008	Adopted by NERC Board of Trustees	
1	March 17, 2011	Order issued by FERC approving IRO- 009-1 (approval effective 5/23/11)	
1	February 28, 201 4	Updated VRFs based on June 24, 2013 approval.	
2			Revised to address the recommendations of the Project 2012-09 Interconnected Reliability Operations Five-Year Review Team.

* FOR INFORMATIONAL PURPOSES ONLY *

Enforcement Dates: Standard IRO-009-1 — Reliability Coordinator Actions to Operate Within IROLs

United States

I

Standard	Requirement	Enforcement Date	Inactive Date
IRO-009-1	All	10/01/2011	