

Implementation Plan for IRO-014-2 — Coordination Among Reliability Coordinators

Prerequisite Approvals

None required

Conforming Changes to Requirements in Already Approved Standards

- IRO-001-2 Reliability Coordination Responsibilities and Authorities
- IRO-015-1 Notifications and Information Exchange Between Reliability Coordinators
- IRO-016-1 Coordination of Real-time Activities between Reliability Coordinators

Revision Summary

• The Reliability Coordination SDT (RC SDT) revised the standard and is proposing retiring two requirements (R3 and R4). New requirements were brought into this standard from IRO-015-1 (R1-R2) and IRO-016-1 (R1 and its sub requirements). Changes were made to eliminate redundancies between standards (existing and proposed), eliminate administrative items, align with NERCs Rules of Procedure and to address issues in FERC Order 693.

Functions that Must Comply with the Requirements in the Standard:

• Reliability Coordinator

Effective Dates

To be determined.

In those jurisdictions where regulatory approval is required, this standard shall become effective one year after applicable regulatory approval. In those jurisdictions where no regulatory approval is required, this standard shall become effective one year after Board of Trustees approval.

Revisions or Retirements to Already Approved Standards

The following tables identify the sections of approved standards that shall be retired or revised when this standard is implemented. If the drafting team is recommending the retirement or revision of a requirement, that text is blue.

Already Approved Standard	Proposed Replacement Requirement(s)
IRO-001-2	IRO-014-2
R7. The Reliability Coordinator shall have clear, comprehensive coordination agreements with adjacent Reliability Coordinators to ensure that System Operating Limit or Interconnection Reliability Operating Limit violation mitigation requiring actions in adjacent Reliability Coordinator Areas are coordinated.	R1. The Each Reliability Coordinator shall have Operating Procedures, Processes, or Plans for activities that require notification, exchange of information or coordination of actions with impacted Reliability Coordinators to support Interconnection reliability. These Operating
	Procedures, Processes, or Plans shall collectively address, as a minimum, the following: [Violation Risk Factor: Medium] [Time Horizon: Same Day Operations and Operations Planning]
	R1.1.1. Communications and notifications, including the mutually agreed to conditions under which one Reliability Coordinator notifies other Reliability Coordinators; the process to follow in making those notifications; and the data and information to be exchanged with other Reliability Coordinators.
	R1.2.1.2. Energy and capacity shortages.
	R1.3.1.3. Planned or unplanned outage information.
	R1.4.1.4. Control of Vvoltage control, including the coordination of reactive resources for voltage control.
	R1.5.1.5. Coordination of information exchange to support reliability assessments.
	R1.6.1.6. Authority to act to prevent and mitigate instances of causing Adverse Reliability Impacts to other Reliability Coordinator Areas.

Notes: The RC_SDT proposes retiring R7 as it is redundant with IRO-014, R1

	Already Approved Standard	Proposed Replacement Requirement(s)
	IRO-014-1	IRO-14-2
	R1. The Reliability Coordinator shall have Operating Procedures, Processes, or Plans in place for activities that require notification, exchange of information or coordination of actions with one or more other Reliability Coordinators to support Interconnection reliability. These Operating Procedures, Processes, or Plans shall address Scenarios that affect other Reliability Coordinator Areas as well as those developed in coordination with other Reliability Coordinators. [Violation Risk Factor: Medium]	R1. The Each Reliability Coordinator shall have Operating Procedures, Processes, or Plans in place for activities that require notification, exchange of information or coordination of actions with impacted with one or more other Reliability Coordinators to support Interconnection reliability. These Operating Procedures, Processes, or Plans shall address Scenarios that affect other Reliability Coordinator Areas as well as those developed in coordination with other Reliability Coordinators. These Operating Procedures, Processes, or Plans shall collectively addressthe following: [Violation Risk Factor: Medium]
	R1.1 These Operating Procedures, Processes, or Plans shall collectively address, as a minimum, the following: [Violation Risk Factor: Lower]	[Time Horizon: Same Day Operations and Operations Planning] R1.1 These Operating Procedures, Processes, or Plans shall collectively
	R1.1.1 Communications and notifications, including the conditions1 under which one Reliability Coordinator notifies other Reliability Coordinators; the process to follow in making those notifications; and the data and information to be exchanged with other Reliability Coordinators. [Violation Risk Factor: Medium]	address, as a minimum, the following: [Violation Risk Factor: Lower] R1.1.1 Communications and notifications, including the mutually agreed to conditions under which one Reliability Coordinator notifies other Reliability Coordinators; the process to follow in making those notifications; and the data and information to be exchanged with other Reliability Coordinators. [Violation]
1	R1.1.2 Energy and capacity shortages. [Violation Risk Factor: Medium]	Risk Factor: Medium]
	R1.1.3 Planned or unplanned outage information. [Violation Risk Factor:	R1.1.2 Energy and capacity shortages. [Violation Risk Factor: Medium]
I	Medium]	R1.1.3 Planned or unplanned outage information. [Violation Risk Factor: Medium]
	R1.1.4 Voltage control, including the coordination of reactive resources for voltage control. [Violation Risk Factor: Medium]	R1.1.4 Control of Vvoltage control, including the coordination of reactive
	R1.1.5 Coordination of information exchange to support reliability assessments. [Violation Risk Factor: Lower]	resources for voltage control. [Violation Risk Factor: Medium] R1.1.5 Coordination of information exchange to support reliability
	R1.1.6 Authority to act to prevent and mitigate instances of causing Adverse Reliability Impacts to other Reliability Coordinator Areas. [Violation Risk Factor: Lower]	assessments. [Violation Risk Factor: Lower] R1.1.6 Authority to act to prevent and mitigate instances of causing Adverse Reliability Impacts to other Reliability Coordinator Areas. [Violation Risk Factor: Lower]
	Notes: Revise R1 as shown and delete the footnote.	

¹ Examples of conditions when one Reliability Coordinator may need to notify another Reliability Coordinator may include (but aren't limited to) sabotage events, Interconnection Reliability Operating Limit violations, voltage reductions, insufficient resources, arming of special protection systems, etc.

Already Approved Standard	Proposed Replacement Requirement(s)
IRO-014-1	IRO-014-2
R2. Each Reliability Coordinator's Operating Procedure, Process, or Plan that requires one or more other Reliability Coordinators to take action (e.g., make notifications, exchange information, or coordinate actions) shall be: R2.1. Agreed to by all the Reliability Coordinators required to take the indicated action(s). R2.2. Distributed to all Reliability Coordinators that are required to take	R2. Each Reliability Coordinator's Operating Procedure, Process, of Plan that requires one or more other Reliability Coordinators to take action (e.g., make notifications, exchange information, or coordinate actions) shall be: [Violation Risk Factor: Lower] [Time Horizon: Real time Operations Planning and Operations Long-term Planning] R2.1 Agreed to by all the Reliability Coordinators required to take
the indicated action(s).	the indicated action(s). [Violation Risk Factor: Lower] R2.2 Distributed to all Reliability Coordinators that are required to take the indicated action(s). [Violation Risk Factor: Lower]

Notes: The RC SDT added a Time Horizon to the requirement and eliminated the VRFs that were applied to the subrequirements.

Already Approved Standard	Proposed Replacement Requirement(s)
IRO-014-1	
R3. A Reliability Coordinator's Operating Procedures, Processes, or Plans developed to support a Reliability Coordinator-to-Reliability Coordinator Operating Procedure, Process, or Plan shall include:	None – Retire the requirement
R3.1. A reference to the associated Reliability Coordinator-to-Reliability Coordinator Operating Procedure, Process, or Plan.	
R3.2. The agreed-upon actions from the associated Reliability Coordinator-to-Reliability Coordinator Operating Procedure, Process, or Plan.	

Notes: This requirement is administrative in nature describing the contents of the plans and should not be in a standard. The RC SDT proposes retiring R3 and its subrequirements and recommends converting these good utility practices into a guideline document for use in developing the operating procedures, processes or plans.

Implementation Plan for IRO-014-2 Coordination Among Reliability Coordinators

Already Approved Standard	Proposed Replacement Requirement(s)
IRO-014-1	None ratire the requirement
R4. Each of the Operating Procedures, Processes, and Plans addressed in Reliability Standard IRO-014 Requirement 1 and Requirement 3 shall:	
R4.1. Include version control number or date.	
R4.2. Include a distribution list.	
R4.3. Be reviewed, at least once every three years, and updated if needed	

Notes: This requirement is administrative in nature describing the contents of the plans and should not be in a standard. The RC SDT proposes retiring R4 and its subrequirements and recommends converting these good utility practices into a guideline document for use in developing the operating procedures, processes or plans.

Already Approved Standard Proposed Replacement Requirement(s) IRO-015-1 IRO-014-2 R1. The Reliability Coordinator shall follow its Operating Procedures, R5R3. The Each Reliability Coordinator shall make notifications and Processes, or Plans for making notifications and exchanging exchange reliability-related information with impacted reliability-related information with other Reliability Coordinators. Reliability Coordinators using its predefined Operating Procedures, Processes, or Plans for conditions that may impact [Violation Risk Factor: Medium] other Reliability Coordinator Areas or other means to R1.1 The Reliability Coordinator shall make notifications to accomplish the notifications and exchange of reliability-related other Reliability Coordinators of conditions in its information. [Violation Risk Factor: Medium] Reliability Coordinator Area that may impact other R6R4. The Each Reliability Coordinator shall participate in agreed Reliability Coordinator Areas. [Violation Risk Factor: Medium1 upon conference calls, at least weekly, and other communication forums with impacted adjacent Reliability R2. The Reliability Coordinator shall participate in agreed upon Coordinators. [Violation Risk Factor: Lower] conference calls and other communication forums with adjacent Reliability Coordinators. [Violation Risk Factor: Lower] R6.1 The frequency of these conference calls shall be agreed upon by all involved Reliability Coordinators and shall be R2.1 The frequency of these conference calls shall be agreed at least weekly. [Violation Risk Factor: Lower] upon by all involved Reliability Coordinators and shall be at least weekly. [Violation Risk Factor: Lower] R3. The Reliability Coordinator shall provide reliability-related information as requested by other Reliability Coordinators. [Violation Risk Factor: Medium]

The RC SDT recommends retiring Standard IRO-015 and moving Requirements R1 and R2 to IRO-014-2 and revising as shown.

The RC SDT proposes retiring R3 (as shown in the left column) as it is redundant with proposed R5 above. Reliability Coordinators already have several requirements aimed at providing data or information to other Reliability Coordinators in support of Reliability Coordinator responsibilities. For example, Reliability Coordinators provide reliability-related information to other Reliability Coordinators as part of IRO-010-1, R3 – they share information as they try to confirm the existence of operating issues as part of IRO-014-2 R5, etc.

Already Approved Standard Proposed Replacement Requirement(s) IRO-016-1 IRO-014-2 R1. The Reliability Coordinator that identifies a potential, expected, or actual R5. When an expected or actual reliability issue is detected. problem that requires the actions of one or more other Reliability Coordinators the Each Reliability Coordinator, upon identification of an shall contact the other Reliability Coordinator(s) to confirm that there is a Adverse Reliability Impact, -shall confirm the existence of the problem and then discuss options and decide upon a solution to prevent or issue with the notify impacted other Reliability Coordinators resolve the identified problem. [Violation Risk Factor: Medium] that are involved. In the event that the issue cannot be confirmed, each RC shall operate as though the problem R1.1 If the involved Reliability Coordinators agree on the problem and the actions to take to prevent or mitigate the system condition, each exists. [Violation Risk Factor: Medium] [Time Horizon: Operations Planning, Same Day Operations and Real-time involved Reliability Coordinator shall implement the agreed-upon solution, and notify the involved Reliability Coordinators of the action(s) Operations] taken. [Violation Risk Factor: Medium] R6. When an expected or actual reliability issue exists and the Each impacted affected Reliability Coordinators shall R1.2 If the involved Reliability Coordinators cannot agree on the operate as though the problem exists when the identified problem(s) each Reliability Coordinator shall re-evaluate the causes of Adverse Reliability Impact cannot be agreed to by the the disagreement (bad data, status, study results, tools, etc.). [Violation impacted Reliability Coordinators can not agree on a Risk Factor: Medium] mitigation plan, all impacted affected Reliability Coordinators R1.2.1 If time permits, this re-evaluation shall be done before shall implement the mitigation plan developed by the taking corrective actions. [Violation Risk Factor: Medium] Reliability Coordinator who has the reliability issue. [Violation] Risk Factor: Medium] [Time Horizon: Operations Planning, R1.2.2 If time does not permit, then each Reliability Coordinator Same Day Operations and Real-time Operations] shall operate as though the problem(s) exist(s) until the conflicting system status is resolved. [Violation Risk Factor: R7. The Reliability Coordinator with the identified Adverse Medium] Reliability Impact shall develop a mitigation plan when the impacted Reliability Coordinators can not agree that the R1.3 If the involved Reliability Coordinators cannot agree on the problem exists. [Violation Risk Factor: Medium][Time solution, the more conservative solution shall be implemented. [Violation Horizon: Operations Planning, Same Day Operations and Risk Factor: Medium] Real-time Operations1 R8. Each impacted Reliability Coordinator shall implement the mitigation plan developed by the Reliability Coordinator who has the identified Adverse Reliability Impact when the impacted Reliability Coordinators can not agree on a mitigation plan. [Violation Risk Factor: Medium][Time Horizon: Operations Planning, Same Day Operations and Real-time Operations1

Implementation Plan for IRO-014-2 Coordination Among Reliability Coordinators

Notes: IRO-014-2 R5 and R6 are revised versions of IRO-016-1, R1 and its subrequirements which were moved to this standard. The RC SDT removed the wording relating to the "most conservative solution" because it can not be measured. We are proposing to use the mitigation plan of the RC who is experiencing the issue in cases where an agreed to mitigation plan can not be developed. Note that stakeholders proposed revisions to these requirements, and the RC SDT subdivided the requirements to add more clarity.